



VAPOR TIGHT CIT401

® 14 5/8" WIDE STEM-MOUNTED VAPOR TIGHT LUMINAIRE


JOB	
TYPE	
DATE	

STEM-MOUNTED VAPOR TIGHT GASKETED LED LUMINAIRE




*Creating any hole in housing or mounting at an angle will invalidate wet location rating.

CROSS SECTION



4' BACKPLATE



SPECIFICATIONS

CONSTRUCTION

- IP65 / IP66 / IP67 / NEMA 4x rated enclosure
- Fiberglass housing with poured-in-place polyurethane gasket
- 22 gauge cold-rolled steel internal snap-on gear tray/cover

FINISH

- Gear tray - baked white polyester finish / minimum reflectance 86%

OPTICAL

- Impact-resistant smooth acrylic frosted lens

ELECTRICAL

- High efficiency drivers coupled with long-life LEDs
- Service life tested at 50,000 hours (L70)
- Universal voltage 120V~277V (347V/480V available)
- Power Factor (PF) ≥ 0.9
- Total Harmonic Distortion (THD) $\leq 20\%$

LISTING

- UL USA and Canada listed
- Suitable for damp locations

WARRANTY

- 5-year limited warranty, 10-year limited warranty available

APPLICATIONS

- Stem-Mounted Applications for Commercial, Refrigeration, Dusty Areas, Freezers, Food Processing

FEATURES

- Rated for wet locations and washdown applications
- 0-10V Dimming driver standard
- Supports California Title 24 compliance
- Rigid mounting beam for stem mounting applications

OPTIONS CONTACT CUSTOMER SERVICE FOR ADDITIONAL OPTIONS

- Range of lumen packages
- High ambient temperature (HT) modules
- Range of lenses
- Sensors and controls
- Second pre-installed watertight hub
- Stainless steel tamper-proof screws
- NSF Splash Zone Certification
- Cord & plug
- Emergency battery pack
- 10 kV surge protector
- Tunable white (2700K - 6500K)
- Customization available upon request



Los Angeles Lighting Mfg. Co.
Contact Us
T: 626-454-8300
F: 626-454-8399
www.lalighting.com
10141 Olney Street
El Monte, CA 91731
Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2024 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED.

Revised 9/9/25



ORDERING INFORMATION

EXAMPLE: CIT401-8-4L-DRFA-WL-BPL1.5-DRDM-UNV-2/840HT

SERIES	NOMINAL LED LUMENS	NOMINAL LENGTH	OPTICAL	RATING	MECHANICAL	CONTROLS / ELECTRICAL	DRIVER	VOLTAGE	# OF LED ROWS	CRI / CCT	AMBIENT TEMP
CIT401		4L		WL					2		
CIT401 • 4 5/8" Wide Stem-Mounted Vapor Tight LED Luminaire	8 - 8000lm 12 - 12000lm 16 - 16000lm 20 - 20000lm 24 - 24000lm High Efficacy 8 - 8000lm 12 - 12000lm 16 - 16000lm	4L • 4'	DRFA • High Impact Smooth Acrylic Frosted Lens FPC • Impact Resistant Frosted Polycarbonate	WL • Wet Location Hardware (Includes 1 Pre-Installed Watertight Hub)	SZ • Wet Location Hardware plus NSF Splash Zone Certification WTHUB • Second Pre-Installed Watertight Hub TP • Stainless Steel Tamper Proof Screws LT • Lens Tethers *Leave blank if not specified	MS(xx) • Motion Sensor • Lens Option WLC(LEDRLU) • Wireless Control BPL1.5 • 1500lm Emergency Battery Pack SP10 • 10 kV Surge Protector *Leave blank if not specified	DRDM • 0-10V Dimming Driver	UNV • 120V - 277V 120V • 120 Volt 277V • 277 Volt 347V • 347 Volt 480V • 480 Volt	2 • 2 LED Rows	827 • 80+CRI / 2700K 830 • 80+CRI / 3000K 835 • 80+CRI / 3500K 840 • 80+CRI / 4000K 850 • 80+CRI / 5000K 865 • 80+CRI / 6500K 8TW • 80+CRI Tunable White 2700K-6500K 90CRI Also available Contact customer service for additional CRI/CCT packages.	HT • High Ambient Temp. *HT cannot be combined with HE systems

Standard options for CIT401 shown above. For additional options, including lumen packages, controls, lenses, switches, finishes, and more, visit www.lalighting.com/resources or contact customer service.

OPTICAL OPTIONS

ADDITIONAL LENSES AVAILABLE. VISIT WWW.LALIGHTING.COM/RESOURCES FOR MORE INFORMATION

STANDARD LENSES FOR CIT401

DRFA	Impact-Resistant Smooth Acrylic Frosted
FPC	Impact-Resistant Polycarbonate Smooth Frosted

ADDITIONAL LENSES FOR CIT401

CPC	Impact-Resistant Clear Polycarbonate
DRCA	Impact-Resistant Smooth Clear Acrylic

MECHANICAL OPTIONS

Pre-installed mechanical options are ordered by adding the suffix to the luminaire description:
CIT401-4-4L-DRFA-WL-WTHUB-DRDM-UNV-2/840

WATERTIGHT HUB
WTHUB

- Zinc die cast hub with rubber gasket seal
- Threaded to fit 1/2" pipe
- One pre-installed hub included on all luminaires
- Second pre-installed hub included when specifying WTHUB

STAINLESS STEEL LATCHES
SSL-CIT401

- Corrosion resistant stainless steel latches
- Twelve (12) latches provided per 4' luminaire

TAMPER PROOF SCREWS
TP

- Hex Pin Stainless Steel Tamper Proof Screws

LENS TETHERS
LT

- Secure lens to enclosure
- Includes two tethers per luminaire
- When ordering separately to install on an existing luminaire, use **CIT4/LT**



Los Angeles Lighting Mfg. Co.

Contact Us

T: 626-454-8300

F: 626-454-8399

www.lalighting.com

10141 Olney Street

El Monte, CA 91731

Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2024 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED.

Revised 9/9/25



MOUNTING ACCESSORIES

Mounting accessories are ordered separately from luminaire


THREADED MOUNTING STEMS

STEM


- 3/8" IPS, nominal OD 5/8"
- Threaded 1" each end
- 2 lock nuts provided per stem
- Standard lengths: 6", 12", 18", 24", 30", 36", 48"
- Baked white enamel finish
- To order, specify length required after STEM.

Example: **STEM12** for 12", **STEM24** for 24", etc.

Other lengths & finishes are available as specified



Stem Length Calculation



SYSTEM DATA

ADDITIONAL LUMEN PACKAGES AVAILABLE. CONTACT CUSTOMER SERVICE FOR MORE INFORMATION

4' - LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
8000 Lumens (Nominal)	CIT401-8-4L-DRFA-DRDM-UNV-2/840	7808	49.5	157.8 lm/W	-20°C / 35°C (-4°F / 95°F)	2x F54T5HO 4x F32T8	*
12000 Lumens (Nominal)	CIT401-12-4L-DRFA-DRDM-UNV-2/840	11528	75.8	152.1 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F54T5HO 6x F32T8	*
16000 Lumens (Nominal)	CIT401-16-4L-DRFA-DRDM-UNV-2/840	15137	103.1	146.8 lm/W	-20°C / 35°C (-4°F / 95°F)	4x F54T5HO	*
20000 Lumens (Nominal)	CIT401-20-4L-DRFA-DRDM-UNV-2/840	18990	122.4	155.2 lm/W	-20°C / 35°C (-4°F / 95°F)	5x F54T5HO	*
24000 Lumens (Nominal)	CIT401-24-4L-DRFA-DRDM-UNV-2/840	22688	149.0	152.2 lm/W	-20°C / 35°C (-4°F / 95°F)	6x F54T5HO	*
4' - LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE (HIGH EFFICACY) PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
8000 Lumens (Nominal)	CIT401-8HE-4L-DRFA-DRDM-UNV-2/840	4043	23.9	169.3 lm/W	-20°C / 35°C (-4°F / 95°F)	2x F54T5HO 4x F32T8	*
12000 Lumens (Nominal)	CIT401-12HE-4L-DRFA-DRDM-UNV-2/840	11430	70.8	161.5 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F54T5HO 6x F32T8	*
16000 Lumens (Nominal)	CIT401-16HE-4L-DRFA-DRDM-UNV-2/840	15238	96.3	158.3 lm/W	-20°C / 35°C (-4°F / 95°F)	4x F54T5HO	*
4' - LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE (HIGH EFFICACY) PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
8000 Lumens (Nominal)	CIT401-8-4L-DRFA-DRDM-UNV-2/840HT	7808	49.5	157.8 lm/W	-30°C / 45°C (-22°F / 113°F)	2x F54T5HO 4x F32T8	*
12000 Lumens (Nominal)	CIT401-12-4L-DRFA-DRDM-UNV-2/840HT	11528	75.8	152.1 lm/W	-30°C / 45°C (-22°F / 113°F)	3x F54T5HO 6x F32T8	*
16000 Lumens (Nominal)	CIT401-16-4L-DRFA-DRDM-UNV-2/840HT	15137	103.1	146.8 lm/W	-20°C / 35°C (-4°F / 95°F)	4x F54T5HO	*
20000 Lumens (Nominal)	CIT401-20-4L-DRFA-DRDM-UNV-2/840HT	18990	122.4	155.2 lm/W	-20°C / 35°C (-4°F / 95°F)	5x F54T5HO	*
24000 Lumens (Nominal)	CIT401-24-4L-DRFA-DRDM-UNV-2/840HT	22688	149.0	152.2 lm/W	-20°C / 35°C (-4°F / 95°F)	6x F54T5HO	*

NOTE:

System data as of 7/7/25 (K-Boards when applicable).
 Luminaire efficiency: 4ft 93.0%
 Subject to change without notice.

System data is based on 120V input voltage. Actual performance may differ as a result of end-user environment and application. This fixture has been tested and listed in accordance with UL Standards.
 L.A. Lighting certifies that it will operate safely when installed properly, and within an ambient temperature range noted in the system data table.

Additional lumen packages and color temperatures available.



Los Angeles Lighting Mfg. Co.

Contact Us
 T: 626-454-8300
 F: 626-454-8399
 www.lalighting.com
 10141 Olney Street
 El Monte, CA 91731
 Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice.
 Please visit our website to view the most current information.

© 2024 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED.

Revised 9/9/25

