



INDUSTRIAL INW200

11" WIDE LENSED INDUSTRIAL STRIP




JOB	
TYPE	
DATE	

SUSPENSION/SURFACE MOUNTED LED LUMINAIRE




- 2" K.O.
- 7/8" K.O.
- 1 1/16" STEM MOUNTING K.O.
- V-HOOK HOLE
- 3/16" MOUNTING HOLE


8' BACKPLATE




4' BACKPLATE



2' BACKPLATE



CROSS SECTION



SPECIFICATIONS

CONSTRUCTION

- 22 gauge cold rolled steel housing
- End plates fastened to housing by screws to assure rigidity

FINISH

- Baked white polyester finish
- Minimum reflectance 86%

OPTICAL

- Frosted white acrylic lens

ELECTRICAL

- High efficiency drivers coupled with long-life LEDs
- Service life tested at 50,000 hours (L70)
- Universal voltage 120V through 277V (347V / 480V available)
- Power Factor (PF) ≥ 0.9
- Total Harmonic Distortion (THD) $\leq 20\%$

LISTING

- UL USA and Canada listed / suitable for damp locations

WARRANTY

5-Year limited warranty standard. 10-Year limited warranty also available

APPLICATIONS

- Warehouse, Industrial, Commercial

FEATURES

- Suitable for damp locations
- 0-10V Dimming driver standard
- Supports California Title 24 compliance

OPTIONS CONTACT CUSTOMER SERVICE FOR ADDITIONAL OPTIONS

- Controls
- Cord & Plug
- 14 gauge wire guard
- Uplight/Slotted reflector
- Custom housing colors
- Emergency battery pack
- 10 kV surge protector
- Customization available upon request

CUSTOM COLORS

BLK - Matte Black

CS - Camaro Silver

BZ - Statuary Bronze



Variety of RAL colors available upon request.



Los Angeles Lighting Mfg. Co.
Contact Us
T: 626-454-8300
F: 626-454-8399
www.lalighting.com
10141 Olney Street
El Monte, CA 91731
Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2025 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED.

Revised: 09/10/25



ORDERING INFORMATION

EXAMPLE: INW200-4-4L-BPL1.5-DRDM-UNV-1/840

SERIES	NOMINAL LED LUMENS	NOMINAL LENGTH	COLOR	MECHANICAL	CONTROLS	ELECTRICAL	DRIVER	VOLTAGE	# OF LED ROWS	CRI / CCT
INW200									1	
INW200 • 11" Wide Lensed Industrial	1 - 1000lm 2 - 2000lm 3 - 3000lm 4 - 4000lm 6 - 6000lm 8 - 8000lm High Efficacy 1HE - 1000lm 2HE - 2000lm 3HE - 3000lm	2L • 2'	BLK • Black BZ • Bronze *Leave blank for standard white	S • Slotted Reflector *Leave blank if not specified	MS(xx) • Motion Sensor • Lens Option WLC(LED RU) • Wireless Control *Leave blank if not specified	BPL1.5 • Emergency Battery Pack 1500 lm SP10 • 10 kV Surge Protector *Leave blank if not specified PIW(xx) • Plug-in Branch Wiring Connector • One or Two Circuit • Low Voltage Dimming C(xx) • Cord 18 ga. 3-wire • Plug Options • NEMA Plug Type • Length of Cord • Location on the fixture	DRDM • 0-10V Dimming Driver	UNV • 120V-277V 120V • 120 Volt 277V • 277 Volt 347V • 347 Volt 480V • 480 Volt	1 • 1 LED Row	827 • 80+CRI / 2700K 830 • 80+CRI / 3000K 835 • 80+CRI / 3500K 840 • 80+CRI / 4000K 850 • 80+CRI / 5000K 865 • 80+CRI / 6500K 8TW • 80+CRI Tunable White 2700K-6500K 90CRI Also available Contact customer service for additional CRI/CCT packages.
	2 - 2000lm 4 - 4000lm 6 - 6000lm 8 - 8000lm 12 - 12000lm 16 - 16000lm High Efficacy 2HE - 2000lm 4HE - 4000lm 6HE - 6000lm	4L • 4'								
	4 - 4000lm 8 - 8000lm 12 - 12000lm 16 - 16000lm 24 - 24000lm High Efficacy 4HE - 4000lm 8HE - 8000lm 12HE - 12000lm	8L • 8'								
	Standard options for INW200 shown above. For additional options, including lumen packages, controls, lenses, switches, finishes, and more, visit www.lalighting.com/resources or contact customer service.									

SYSTEM DATA

ADDITIONAL LUMEN PACKAGES AVAILABLE. CONTACT CUSTOMER SERVICE FOR MORE INFORMATION

2' - LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
1000 Lumens (Nominal)	INW200-1-2L-DRDM-UNV-1/840	1139	7.5	151.9 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F17T8	*
2000 Lumens (Nominal)	INW200-2-2L-DRDM-UNV-1/840	1870	12.7	146.9 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F24T5HO 2x F17T8	*
3000 Lumens (Nominal)	INW200-3-2L-DRDM-UNV-1/840	2937	20.9	140.6 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F17T8	*
4000 Lumens (Nominal)	INW200-4-2L-DRDM-UNV-1/840	3626	26.5	136.7 lm/W	-20°C / 35°C (-4°F / 95°F)	2x F24T5HO 4x F17T8	*
6000 Lumens (Nominal)	INW200-6-2L-DRDM-UNV-1/840	5523	39.0	141.6 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F24T5HO 6x F17T8	*
8000 Lumens (Nominal)	INW200-8-2L-DRDM-UNV-1/840	7261	52.4	138.7 lm/W	-20°C / 35°C (-4°F / 95°F)	2x F54T5HO 4x F24T5HO	*
2' - LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE (HIGH EFFICACY) PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
1000 Lumens (Nominal)	INW200-1HE-2L-DRDM-UNV-1/840	1157	7.4	156.5 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F17T8	*
2000 Lumens (Nominal)	INW200-2HE-2L-DRDM-UNV-1/840	1906	12.4	153.2 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F24T5HO 2x F17T8	*
3000 Lumens (Nominal)	INW200-3HE-2L-DRDM-UNV-1/840	3013	20.2	149.2 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F17T8	*



Los Angeles Lighting Mfg. Co.

Contact Us

 T: 626-454-8300
 F: 626-454-8399
www.lalighting.com

 10141 Olney Street
 El Monte, CA 91731
 Made in the USA


Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2025 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED.

Revised: 09/10/25

MADE IN THE USA
BAA/BABA Compliant

SYSTEM DATA

ADDITIONAL LUMEN PACKAGES AVAILABLE. CONTACT CUSTOMER SERVICE FOR MORE INFORMATION

4' - LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
2000 Lumens (Nominal)	INW200-2-4L-DRDM-UNV-1/840	1895	12.4	152.3 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F32T8	*
4000 Lumens (Nominal)	INW200-4-4L-DRDM-UNV-1/840	3719	25.5	146.0 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F54T5HO 2x F32T8	*
6000 Lumens (Nominal)	INW200-6-4L-DRDM-UNV-1/840	5490	39.0	140.8 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F32T8	*
8000 Lumens (Nominal)	INW200-8-4L-DRDM-UNV-1/840	7209	53.1	135.9 lm/W	-20°C / 35°C (-4°F / 95°F)	2x F54T5HO 4x F32T8	*
12000 Lumens (Nominal)	INW200-12-4L-DRDM-UNV-1/840	10980	78.0	140.8 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F54T5HO 6x F32T8	*
16000 Lumens (Nominal)	INW200-16-4L-DRDM-UNV-1/840	14435	97.9	147.4 lm/W	-20°C / 35°C (-4°F / 95°F)	4x F54T5HO	*
4' - LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE (HIGH EFFICACY) PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
2000 Lumens (Nominal)	INW200-2HE-4L-DRDM-UNV-1/840	1926	12.3	156.7 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F32T8	*
4000 Lumens (Nominal)	INW200-4HE-4L-DRDM-UNV-1/840	3789	24.9	152.3 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F54T5HO 2x F32T8	*
6000 Lumens (Nominal)	INW200-6HE-4L-DRDM-UNV-1/840	5626	37.8	149.0 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F32T8	*

8' - LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
4000 Lumens (Nominal)	INW200-4-8L-DRDM-UNV-1/840	3752	24.9	150.8 lm/W	-20°C / 35°C (-4°F / 95°F)	2x F32T8	*
8000 Lumens (Nominal)	INW200-8-8L-DRDM-UNV-1/840	7365	50.9	144.6 lm/W	-20°C / 35°C (-4°F / 95°F)	2x F54T5HO 4x F32T8	*
12000 Lumens (Nominal)	INW200-12-8L-DRDM-UNV-1/840	10873	78.0	139.4 lm/W	-20°C / 35°C (-4°F / 95°F)	6x F32T8 2x F96T8HO	*
16000 Lumens (Nominal)	INW200-16-8L-DRDM-UNV-1/840	14277	106.1	134.5 lm/W	-20°C / 35°C (-4°F / 95°F)	4x F54T5HO 8x F32T8	*
24000 Lumens (Nominal)	INW200-24-8L-DRDM-UNV-1/840	21399	153.4	139.5 lm/W	-20°C / 35°C (-4°F / 95°F)	6x F54T5HO 4x F96T8HO	*
8' - LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE (HIGH EFFICACY) PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
4000 Lumens (Nominal)	INW200-4HE-8L-DRDM-UNV-1/840	3813	24.6	155.1 lm/W	-20°C / 35°C (-4°F / 95°F)	2x F32T8	*
8000 Lumens (Nominal)	INW200-8HE-8L-DRDM-UNV-1/840	7137	47.2	151.3 lm/W	-20°C / 35°C (-4°F / 95°F)	2x F54T5HO 4x F32T8	*
12000 Lumens (Nominal)	INW200-12HE-8L-DRDM-UNV-1/840	10781	72.8	148.0 lm/W	-20°C / 35°C (-4°F / 95°F)	6x F32T8 2x F96T8HO	*

NOTE:

System data as of 6/3/25 (K-Boards when applicable).
 Luminaire efficiency: 2ft - 89.4%, 4ft - 88.9%, 8ft - 88%
 Subject to change without notice.

System data is based on 120V input voltage. Actual performance may differ as a result of end-user environment and application. This fixture has been tested and listed in accordance with UL Standards. L.A. Lighting certifies that it will operate safely when installed properly, and within an ambient temperature range noted in the system data table.

Additional lumen packages and color temperatures available.



Los Angeles Lighting Mfg. Co.
 Contact Us
 T: 626-454-8300
 F: 626-454-8399
 www.lalighting.com
 10141 Olney Street
 El Monte, CA 91731
 Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.


© 2025 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED.

Revised: 09/10/25




MOUNTING ACCESSORIES


Y-TOGGLE-END / CABLE SUSPENSION SYSTEM



CABLE SUSPENSION SYSTEM



V-HOOK / CABLE SUSPENSION SYSTEM





V-HOOK

- Hooks attach to V-Hook Holes on luminaire or chain mount coupling tabs
- Two (2) required per luminaire

FOR FIXTURE SERIES	CAT. NO
4" LEG HEIGHT (110/200/240/500) Series	V4
6" LEG HEIGHT (300/400) Series	V6

CANOPY / CABLE SUSPENSION SYSTEM

- Self-locking, one-step adjustable suspension device with canopy



CHAIN MOUNT COUPLING

- Chain mount coupling with lift-up tabs for installation of V-Hooks when chain mounted
- Baked white enamel finish



LUMINAIRE MODEL	CAT. NO.
INW200	CMC-XXW200



Los Angeles Lighting Mfg. Co.

Contact Us

T: 626-454-8300

F: 626-454-8399

www.lalighting.com

10141 Olney Street

El Monte, CA 91731

Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2025 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED.

Revised: 09/10/25

