



WRAPAROUND WH0200


® HIGH IMPACT WRAPAROUND LUMINAIRE




JOB	
TYPE	
DATE	

CEILING/SUSPENSION MOUNTED


DIMENSIONS




CROSS SECTION



4' BACKPLATE



8' BACKPLATE



◆ 11/16" STEM MTG. K.O. ⊕ 7/8" K.O. ⊕ 2" K.O.

SPECIFICATIONS

CONSTRUCTION

- 22 gauge cold-rolled steel welded housing

FINISH

- Painted after fabrication
- Baked white powder-coated finish
- Minimum reflectance 90%

OPTICAL

- High-impact clear prismatic acrylic lens (minimum thickness 0.125")
- Lens secured by spring-loaded barrel latches

ELECTRICAL

- High-efficiency drivers coupled with long-life LEDs
- Service life greater than 50,000 hours (L70)
- Universal voltage 120V ~ 277V (347V / 480V available)
- Power Factor (PF) ≥ 0.9
- Total Harmonic Distortion (THD) ≤ 20%

LISTING

- UL USA and Canada listed / suitable for damp locations

WARRANTY

- 5-Year limited warranty standard. 10-Year limited warranty also available

APPLICATIONS

- Commercial, Classrooms, Offices, Corridors, Public Areas

FEATURES

- Surface / pendant mounted LED luminaire
- 0-10V dimming driver standard (other dimming types available)
- Controls and sensors available
- Wireless control options
- Supports California Title 24 compliance
- Suitable for damp locations
- Additional lumen packages and color temperatures available

OPTIONS CONTACT CUSTOMER SERVICE FOR ADDITIONAL OPTIONS

- Controls
- Cord & plug
- Emergency battery pack
- Customization available upon request



Los Angeles Lighting Mfg. Co.

Contact Us

T: 626-454-8300

F: 626-454-8399

www.lalighting.com

10141 Olney Street

El Monte, CA 91731

Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2024 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED.

Revised: 07/23/25



ORDERING INFORMATION

ORDERING INFORMATION: Additional Options Available. Visit www.lalighting.com/resources for more information

EXAMPLE: WHO200-2-4L-DRP3-BPL1.5-DRDM-UNV-1/840

SERIES	NOMINAL LED LUMENS	NOMINAL LENGTH	OPTICAL	ELECTRICAL	DRIVER	VOLTAGE	# OF LED ROWS	CRI / CCT
WHO200							2	
WHO200 • High Impact Wraparound LED Luminaire	3 - 3000lm 4 - 4000lm 6 - 6000lm 4 - 4000lm 6 - 6000lm 8 - 8000lm 12 - 12000lm	4L • 4' 8L • 8'	DRP3 High-Impact Clear Prismatic Acrylic Lens. Min. thickness 0.125"	BPL1.5 • 1500 lm emergency battery pack MSH • Microwave Motion Sensor-On/Off MSHSD • Microwave Motion Sensor-High/Low WLC(LED RU) • EnOcean Zone Controller *Leave blank if not specified	DRDM • 0-10V Dimming Driver DRDM2C • 2-Channel 0-10V Dimming Driver (for Color Tunable White) DRSD • Step Dimming Driver DR2W • 120V 2-Wire Phase Dimming Driver (Must Specify 120V in Voltage Column)	UNV • 120V-277V 120V • 120 Volt 277V • 277 Volt	2 • Two LED Rows	827 • 80+CRI / 2700K 830 • 80+CRI / 3000K 835 • 80+CRI / 3500K 840 • 80+CRI / 4000K 850 • 80+CRI / 5000K 865 • 80+CRI / 6500K 8TW • 80+CRI Tunable White 2700K-6500K Requires DRDM2C driver 90CRI Also available Contact customer service for additional CRI/CCT packages.

Most common options for WHO200 shown above. For additional options, including lumen packages, controls, lenses, colors/finishes, cord & plug, switches, and more visit www.lalighting.com/resources or contact customer service.

SENSORS AND CONTROLS

High Frequency (Microwave) Motion Sensors

Detects movement through low density materials, including polycarbonate, acrylic and glass diffusers.

MSH - Microwave Motion Sensor – On/Off

- Turns luminaire on/off in response to motion

MSHSD - Microwave Motion Sensor – High/Low

- Increases/decreases illumination in response to motion

Zone Controller

WLC(LED RU) - LED Relay Zone Controller

- Pre-installed inside luminaire
- Can support a single luminaire or multiple daisy-chained luminaires



Los Angeles Lighting Mfg. Co.
 Contact Us
 T: 626-454-8300
 F: 626-454-8399
www.lalighting.com
 10141 Olney Street
 El Monte, CA 91731
 Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2023 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED.

Revised: 07/23/25





MOUNTING HARDWARE

STEM (Specify Length)

- 3/8" IPS, nominal OD 5/8"
- Threaded 1" each end
- 2 lock nuts provided per stem
- Standard lengths: 6", 12", 18", 24", 30", 36", 48"
- Baked white enamel finish

Other lengths & finishes are available as specified

**Stem Length Calculation****CANOPY / CABLE SUSPENSION SYSTEM**

- Self-locking, one-step adjustable suspension device with canopies
- Provides full 360° rotation

**433B**

- Canopy with cable
- No power cord
- Cable length 48" and 96"
- Max. Weight 196 lbs.

433B-48 W**COLOR**

W - White
B - Black

CABLE LENGTH

48 - 48 inches
96 - 96 inches
 (other lengths as specified)

**444F**

- Feed-in canopy with straight cord
- Includes power cord
- Cable length 48" and 96"
- Max. Weight 196 lbs

444F-48SW-2C**# OF CIRCUITS**

2C - Two circuits
LV - 0-10V dimming
Blank - One circuit

COLOR

W - White
B - Black

CORD TYPE

S - Straight cord

CABLE LENGTH

48 - 48 inches
96 - 96 inches
 (other lengths as specified)



Los Angeles Lighting Mfg. Co.

Contact Us

T: 626-454-8300
 F: 626-454-8399
 www.lalighting.com

10141 Olney Street
 El Monte, CA 91731
 Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2023 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED.

Revised: 07/23/25



SYSTEM DATA

ADDITIONAL LUMEN PACKAGES AVAILABLE. CONTACT CUSTOMER SERVICE FOR MORE INFORMATION

4' - LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
3000 Lumens (Nominal)	WHO200-3-4L-DRP3-DRDM-UNV-2/840	2683	16.8	159.7 lm/W	-20°C / 35°C (-4°F / 95°F)	2x F32T8	*
4000 Lumens (Nominal)	WHO200-4-4L-DRP3-DRDM-UNV-2/840	3802	24.2	157.3 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F54T5HO 2x F32T8	*
6000 Lumens (Nominal)	WHO200-6-4L-DRP3-DRDM-UNV-1/840	5645	36.7	153.9 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F32T8	*

8' - LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
4000 Lumens (Nominal)	WHO200-4-8L-DRP3-DRDM-UNV-1/840	3867	23.9	161.9 lm/W	-20°C / 35°C (-4°F / 95°F)	2x F32T8	*
6000 Lumens (Nominal)	WHO200-6-8L-DRP3-DRDM-UNV-1/840	5370	33.6	159.8 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F32T8	*
8000 Lumens (Nominal)	WHO200-8-8L-DRP3-DRDM-UNV-1/840	7238	45.8	158.0 lm/W	-20°C / 35°C (-4°F / 95°F)	2x F54T5HO 4x F32T8	*
12000 Lumens (Nominal)	WHO200-12-8L-DRP3-DRDM-UNV-1/840	10934	70.8	154.5 lm/W	-20°C / 35°C (-4°F / 95°F)	6x F32T8 2x F96T8HO	*

NOTE:

System data as of 07/23/25 (K-Boards when applicable).

Luminaire efficiency: 4ft 89.2%, 8ft 89.2%

Subject to change without notice.

System data is based on 120V input voltage. Actual performance may differ as a result of end-user environment and application. This fixture has been tested and listed in accordance with UL Standards.

L.A. Lighting certifies that it will operate safely when installed properly, and within an ambient temperature range noted in the system data table.

Additional lumen packages and color temperatures available.

**Los Angeles Lighting Mfg. Co.**

Contact Us

T: 626-454-8300

F: 626-454-8399

www.lalighting.com

10141 Olney Street

El Monte, CA 91731

Made in the USA



Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2023 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED.

Revised: 07/23/25

MADE IN THE USA
BABA/BAA Compliant