

CLEANROOM LED
GCR720
CLASS 1000/10000 CLEANROOM GRID LUMINAIRE

JOB	
TYPE	
DATE	

Grid-Mounted



COMPATIBLE T-BAR GRIDS	
WIDTH	HEIGHT
15/16"	1 1/2"
1 1/2"	1 1/2"




2' x 4'




2' x 2'

CROSS SECTION




4' BACKPLATE



2' BACKPLATE

7/8" KO



SPECIFICATIONS

Construction
- Class 1000/10,000 (ISO Class 6/7 Equivalent)
- 22 gauge cold-rolled steel welded housing
- 20 gauge cold-rolled steel door frame secured by T-hinges and spring-loaded latches
- All parts fitted and sealed
- Door frame sealed with closed cell neoprene gasket

Finish
- Painted after fabrication
- Baked white powder-coated finish
- Minimum reflectance 90%

Optical
- Inverted clear prismatic acrylic lens (nominal 0.125" thickness)

Electrical
- High efficiency drivers coupled with long-life LEDs
- Service life greater than 50,000 hours (L70)
- Universal voltage 120V through 277V (347V / 480V available)
- Power Factor (PF) ≥ 0.9
- Total Harmonic Distortion (THD) ≤ 20%

Listing
- UL USA and Canada listed / suitable for damp locations

Warranty
- 5-Year limited warranty standard. 10-Year limited warranty also available

APPLICATIONS

- Cleanroom, Sealed Ceiling Areas, Commercial

FLAT PANEL option

FEATURES

- Made in America, BABA & BAA Compliant
- 0-10V dimming driver standard
- Supports California Title 24 compliance

OPTIONS

- Range of lumen packages and color temperatures
- Flat panel optics
- Tunable white (2700K - 6500K)
- Colored LEDs, including True/Native Amber
- Sensors and controls
- Lens options
- Antimicrobial finish
- Emergency battery pack
- Customization available upon request

Los Angeles Lighting Mfg. Co.
Contact Us
T: 626-454-8300
F: 626-454-8399
www.lalighting.com
10141 Olney Street
El Monte, CA 91731
Made in the USA

ROHS COMPLIANT · UL CERTIFIED

Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice. Please visit our website to view the most current information.

© 2025 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED

Revised: 09/26/25

BAA BABA compliant

ORDERING INFORMATION

Visit www.lalighting.com/resources for additional options.

EXAMPLE: GCR720-4-4L-FSW-PA2-BPL1.5-DRDM-UNV-2/840


SERIES	NOMINAL LED LUMENS	NOMINAL LENGTH	FINISH	DOOR FRAME	OPTICAL	ELECTRICAL	DRIVER	VOLTAGE	LED LAYOUT	CRI / CCT
GCR720										
GCR720 • Class 1000/10000 Cleanroom Grid LED Luminaire	**2** - 2000 lm **4** - 4000 lm **6** - 6000 lm **8** - 8000 lm **12** - 12000 lm **High Efficacy** **2HE** - 2000 lm **4HE** - 4000 lm **6HE** - 6000 lm **8HE** - 8000 lm	**2L** • 2'	**AMF** • Antimicrobial Finish *Leave blank if not specified	**FSW** • Flat Steel White Enamel Door Frame	**PA2** • Clear Prismatic Acrylic 0.125" **FPA2** • Frosted Prismatic Acrylic 0.125" **DRP8** • High-Impact Clear Prismatic Acrylic 0.187" **FFWA** • Flat Frosted White Acrylic	**BPL1.5** • 1500 lm emergency battery pack *Leave blank if not specified	**DRDM** • 0-10V Dimming Driver **DRDM2C** • 2-Channel 0-10V Dimming Driver (for Color Tunable White) **DRSD** • Step Dimming Driver **DR2W** • 120V 2-Wire Phase Dimming Driver (Must Specify 120V in Voltage Column)	**UNV** • 120V-277V **120V** • 120 Volt **277V** • 277 Volt	**2** • Two Rows **P4** • Flat Panel (Must specify FFWA in optical coumn)	**827** • 80+CRI / 2700K **830** • 80+CRI / 3000K **835** • 80+CRI / 3500K **840** • 80+CRI / 4000K **850** • 80+CRI / 5000K **865** • 80+CRI / 6500K **8TW** • 80+CRI Tunable White 2700K-6500K Requires DRDM2C driver **AM8**[1] • PC Yellow 575 nm - 590 nm **AM9**[1] • PC Amber 586 nm - 593 nm **AMT**[1] • True Amber 585 nm - 595 nm **90CRI Also available** Contact customer service for additional CRI/CCT packages.
	2 - 2000 lm **4** - 4000 lm **6** - 6000 lm **8** - 8000 lm **12** - 12000 lm **High Efficacy** **2HE** - 2000 lm **4HE** - 4000 lm **6HE** - 6000 lm **8HE** - 8000 lm **12HE** - 12000 lm	**4L** • 4'								

Standard options for GCR720 shown above. For additional options, including lumen packages, controls, lenses, switches, finishes, and more, visit www.lalighting.com/resources or contact customer service.

1 For amber and other color LEDs, available lumen packages vary. Contact customer service for more information.

DOOR FRAME

CROSS SECTION



FEATURES

- T-Hinges and Positive Spring Loaded Latches
- Inverted Lens
- Sealed with Closed Cell Neoprene Gasket
- Light Stop Covers Installed
- Internal Frame Rail (FS only)

FS **W**

FINISHES

W White Enamel
B Black Enamel
N Natural Anodized Aluminum (only available for FA and RA styles)

STYLES

FS Flat Steel
FA Flat Extruded Aluminum
RA 5/8" Regressed Extruded Aluminum

OPTICAL OPTIONS

STANDARD LENSES FOR GCR720 - Prismatic lenses are inverted to position the flat side facing down.

PA2 Clear Prismatic Acrylic, Nom. 0.125” OA Thickness, Female Prisms 3/16” Square Base, Pattern 12

FPA2 Frosted Prismatic Acrylic, Nom. 0.125” OA Thickness, Female Prisms 3/16” Square Base, Pattern 12

DRP8 High-Impact Clear Prismatic Acrylic, Nom. 0.187” OA Thickness, Female Prisms 3/16” Square Base, Pattern 12

FFWA Flat Frosted White Acrylic, No Thickness Specified

Los Angeles Lighting Mfg. Co.
Contact Us
T: 626-454-8300
F: 626-454-8399
www.lalighting.com
10141 Olney Street
El Monte, CA 91731
Made in the USA

Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice.
Please visit our website to view the most current information.
© 2025 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED

Revised: 09/26/25

SYSTEM DATA: Additional Lumen Packages Available. Contact Customer Service for More Information

Normal Temp

2' LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
2000 Lumens (Nominal)	GCR720-2-2L-FSW-PA2-DRDM-UNV-2/840	1548	12.5	124.2 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F24T5HO 2x F17T8	*
4000 Lumens (Nominal)	GCR720-4-2L-FSW-PA2-DRDM-UNV-2/840	3039	25.5	119.0 lm/W	-20°C / 35°C (-4°F / 95°F)	2x F24T5HO 4x F17T8	*
6000 Lumens (Nominal)	GCR720-6-2L-FSW-PA2-DRDM-UNV-2/840	4443	39.1	113.7 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F24T5HO 6x F17T8	*
8000 Lumens (Nominal)	GCR720-8-2L-FSW-PA2-DRDM-UNV-2/840	5889	53.1	111.0 lm/W	-20°C / 35°C (-4°F / 95°F)	2x F54T5HO 4x F24T5HO	*
12000 Lumens (Nominal)	GCR720-12-2L-FSW-PA2-DRDM-UNV-2/840	8880	78.0	113.8 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F54T5HO 6x F24T5HO	*

Normal Temp High Efficacy

2' LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE (HIGH EFFICACY) PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
2000 Lumens (Nominal)	GCR720-2HE-2L-FSW-PA2-DRDM-UNV-2/840	1574	12.3	128.0 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F24T5HO 2x F17T8	*
4000 Lumens (Nominal)	GCR720-4HE-2L-FSW-PA2-DRDM-UNV-2/840	3097	24.9	124.5 lm/W	-20°C / 35°C (-4°F / 95°F)	2x F24T5HO 4x F17T8	*
6000 Lumens (Nominal)	GCR720-6HE-2L-FSW-PA2-DRDM-UNV-2/840	4598	37.8	121.7 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F24T5HO 6x F17T8	*
8000 Lumens (Nominal)	GCR720-8HE-2L-FSW-PA2-DRDM-UNV-2/840	6162	50.9	121.0 lm/W	-20°C / 35°C (-4°F / 95°F)	2x F54T5HO 4x F24T5HO	*

Normal Temp

4' LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
2000 Lumens (Nominal)	GCR720-2-4L-FSW-PA2-DRDM-UNV-2/840	1682	12.4	136.2 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F32T8	*
4000 Lumens (Nominal)	GCR720-4-4L-FSW-PA2-DRDM-UNV-2/840	3353	24.9	134.4 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F54T5HO 2x F32T8	*
6000 Lumens (Nominal)	GCR720-6-4L-FSW-PA2-DRDM-UNV-2/840	4978	37.8	131.8 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F32T8	*
8000 Lumens (Nominal)	GCR720-8-4L-FSW-PA2-DRDM-UNV-2/840	6581	50.9	129.2 lm/W	-20°C / 35°C (-4°F / 95°F)	2x F54T5HO 4x F32T8	*
12000 Lumens (Nominal)	GCR720-12-4L-FSW-PA2-DRDM-UNV-2/840	9599	78.0	123.1 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F54T5HO 6x F32T8	*

Normal Temp High Efficacy

4' LED LUMEN PACKAGE	NORMAL AMBIENT TEMPERATURE (HIGH EFFICACY) PRODUCT CODE	DELIVERED LUMENS	SYSTEM WATTS	LUMINAIRE EFFICACY	AMBIENT TEMP.	FLUORESCENT EQUIVALENT	IES FILES
2000 Lumens (Nominal)	GCR720-2HE-4L-FSW-PA2-DRDM-UNV-2/840	1741	12.2	142.3 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F32T8	*
4000 Lumens (Nominal)	GCR720-4HE-4L-FSW-PA2-DRDM-UNV-2/840	3407	24.6	138.6 lm/W	-20°C / 35°C (-4°F / 95°F)	1x F54T5HO 2x F32T8	*
6000 Lumens (Nominal)	GCR720-6HE-4L-FSW-PA2-DRDM-UNV-2/840	4732	34.6	136.8 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F32T8	*
8000 Lumens (Nominal)	GCR720-8HE-4L-FSW-PA2-DRDM-UNV-2/840	6377	47.2	135.2 lm/W	-20°C / 35°C (-4°F / 95°F)	2x F54T5HO 4x F32T8	*
12000 Lumens (Nominal)	GCR720-12HE-4L-FSW-PA2-DRDM-UNV-2/840	9512	72.8	130.6 lm/W	-20°C / 35°C (-4°F / 95°F)	3x F54T5HO 6x F32T8	*

NOTE:
System data as of 12/26/24 (K-Boards).
Luminaire efficiency: 2x2 - 72.6%, 2x4 - 78.6%
Subject to change without notice.

System data is based on 120V input voltage. Actual performance may differ as a result of end-user environment and application. This fixture has been tested and listed in accordance with UL Standards. L.A. Lighting certifies that it will operate safely when installed properly, and within an ambient temperature range noted in the system data table.

Additional lumen packages and color temperatures available.

LA LIGHTING®
Los Angeles Lighting Mfg. Co.
Contact Us
T: 626-454-8300
F: 626-454-8399
www.lalighting.com
10141 Olney Street
El Monte, CA 91731
Made in the USA

RoHS COMPLIANT CERTIFIED

Due to continued product improvements and enhancements, Los Angeles Lighting Manufacturing Company reserves the right to alter specifications, dimensions, data, and/or materials without notice.
Please visit our website to view the most current information.
© 2025 LOS ANGELES LIGHTING MANUFACTURING CO. ALL RIGHTS RESERVED

Revised: 09/26/25

BAA BABA compliant